

**Certification  
Issued Under the Authority of the  
Federal Communications Commission**

**By:**

**MiCOM Labs  
575 Boulder Court  
Pleasanton, CA 94566**

**Date of Grant: 10/12/2016  
Application Dated: 10/12/2016**

**Mikrotikls SIA  
Pernavas 46  
Riga, LV-1009  
Latvia**

**Attention: Edmunds Zvegincevs , engineer, R&D**

**NOT TRANSFERABLE**

EQUIPMENT AUTHORIZATION is hereby issued to the named GRANTEE, and is VALID ONLY for the equipment identified hereon for use under the Commission's Rules and Regulations listed below.

**FCC IDENTIFIER:** TV70MNITIKPG5HACD  
**Name of Grantee:** Mikrotikls SIA  
**Equipment Class:** Unlicensed National Information Infrastructure TX  
**Notes:** The OmniTIK 5 PoE ac is a weatherproof outdoor Access Point with dual-polarized omni antennas.

<u>Grant Notes</u>	<u>FCC Rule Parts</u>	<u>Frequency Range (MHZ)</u>	<u>Output Watts</u>	<u>Frequency Tolerance</u>	<u>Emission Designator</u>
38 MO	15E	5180.0 - 5240.0	0.035		
38 MO	15E	5745.0 - 5825.0	0.398		

Power listed is the maximum combined output power. Device is 2X2 MIMO. This device contains 20, 40 and 80 MHz signal bandwidth. The antenna(s) used for this transmitter must be installed to provide a separation distance of at least 20 cm from all persons and must not be co-located or operating in conjunction with any other antenna or transmitter, except in accordance with FCC multi-transmitter product procedures. End-users must be provided with transmitter operating conditions for satisfying RF exposure compliance.

- 38: This device has shown compliance, in all grant-listed U-NII sub-bands, with the new rules for U-NII devices adopted under Docket No. 13-49 and may be marketed, manufactured or imported after the June 1, 2016 transition deadline.
- MO: This Multiple Input Multiple Output (MIMO) device was evaluated for multiple transmitted signals as indicated in the filing.

